



Features

- Multimode or single-mode applications
- Wave ID (auto identification/switching)
- Multiple-wavelength testing
- 270 Hz, 330 Hz, 1 kHz, 2 kHz tone detection
- Large LCD with backlight
- Power measurements in dBm or μ W; insertion loss in dB
- Reference power level storage
- File management system organizes stored test data
- Storage capability > 500 fibers
- USB port and Windows® compatible software for download of stored data
- Automatic power-off function
- Battery gauge
- Long battery life with 2 x AA alkaline, optional AC adapter
- Hand-held, rugged, lightweight

NOYES® OPM5 Optical Power Meter

With Innovative File Management System

The new NOYES OPM5 is a full-featured, hand-held optical power meter designed for measuring optical power in premise, Telco, or broadband networks and for performing insertion loss measurements on multimode or single-mode fiber optic links. The standard Wave ID feature (when used with NOYES OLS series light sources) automatically detects and sets the wavelength(s), preventing setup and measurement errors. It significantly increases efficiency and reduces technician errors—and saves testing time—by eliminating the need to test each wavelength individually. The OPM5 stores optical references for each calibrated wavelength and offers multiple test tone detection for fiber identification. The OPM5 is fully N.I.S.T. traceable.

Data Storage of Test Results

The OPM5 File Management system allows technicians to organize test results into multiple files and transfer stored results via USB to a PC for analyzing, generating reports, and printing. The supplied powerful PC Analysis and Reporting Tool (TRM™ - Test Results Management software) allows users to apply industry standards based rules to test results and create comprehensive certification reports. Users can generate network Pass/Fail results demonstrating compliance to industry standards and illustrate headroom. TRM is a Windows® compatible software

Applications

- Passive Optical Networks (PON) testing
- Save test data for Report Generation with NOYES TRM Software
- OPM5-2D (Ge) for Premises LAN/WAN multimode or single-mode networks
- OPM5-3D (InGaAs) for Telecommunications networks
- OPM5-4D (Filtered-InGaAs) for high power (+26 dBm) CATV Broadband networks or DWDM system applications

NOYES®

OPM5 Optical Power Meter with PC Reporting Tool – TRM™



Powerful Pair

The OPM5 Optical Power Meter and TRM Test Results Management software is a powerful pair

- Increases efficiency
- Reduces technician errors
- Simple to operate with minimal training required
- Provides customized professional reports

Target Markets

Any one testing fiber links who requires report generation applications include

- Data networks
- Telecommunications providers
- CATV
- Industrial

WaveID Increases Efficiency and Reduces Errors

- Enables users to test two wavelengths simultaneously
 - Significantly reduces test time by eliminating the need to test each wavelength individually
- Automatically detects and sets received wavelengths
 - Eliminates loss measurement errors by automatically matching OPM to transmitted wavelength

Straightforward Results Storage and Easy File Management in the Field

- Simple to use interface allows for easy separation of results into files
- Keep cable/job results separated for fast customer report generation
- Access to files and results allows for quick and easy retest of fibers

NOYES®

Upload test data files to PC via USB to utilize powerful data management and reporting tool – TRM™

File Naming and Data Management Editor

- Manage job information (Ends, Cable ID, Comments, and Operators) to meet documentation specifications in reports
- Create Bi-directional results
- Combine results from multiple OPMs to create a complete job report
- Automatic backup of data

Create Certification Results to Industry Standards (TIA/ISO/EN and applications)

- Apply standards based rules to loss results
- Generate Pass/Fail information for each fiber
- Demonstrate compliance to industry standards

Customized Reports

- Create professional personalized reports with company logos
- Reports meet accepted industry documentation standards.
- Save common report options for quick generation of future reports
- Recall previously stored settings to save time generating reports for repeat customers
- Create certification reports showing fiber pass/fail results based on customer/consultant specifications, Industry Standard, and Industry Applications
- Show headroom values for the primary rule (typically the industry standard)
- Use PC analysis to verify if previously measured fibers (tested with NOYES loss test equipment) meet loss requirements of Standards and Rules

Superior Customer Support

- Dedicated customer service, technical support and field sales available to support customers
- Knowledgeable timely technical support and customer service

The screenshot displays the NOYES TRM software interface. On the left, a sidebar shows job details for 'Job1 Loc1_Loc2 File1'. The main area contains several data tables:

Fiber	1310nm A->Z	1550nm A->Z
1	2.63 dB	-2.07 dB
2	2.38 dB	2.56 dB
3	2.42 dB	2.62 dB
4	2.56 dB	2.79 dB
5	2.36 dB	2.52 dB
6	2.52 dB	2.75 dB
7	2.52 dB	2.75 dB
8	2.43 dB	2.63 dB
9	2.52 dB	2.74 dB
10	2.71 dB	2.98 dB
11	2.65 dB	2.91 dB
12	2.36 dB	2.54 dB
13	2.60 dB	2.85 dB

Below this is a 'BiDirectional Data' table with columns for 1310nm A->Z, 1310nm Z->A, and 1550nm A->Z. A 'Certification Results' panel on the right shows a 'Cabling Standard' of ISO 11801 (International Standard) and a 'Pass' status for all fibers. A detailed table below shows test dates, times, fiber IDs, loss values, and pass/fail status for each fiber.

NOYES®
OPM5 Optical Power Meter

Specifications ^a

OPTICAL	OPM5-2D	OPM5-3D	OPM5-4D
Calibrated Wavelengths	850, 1300, 1310, 1490, 1550 nm	850, 1300, 1310, 1550, 1490, 1625 nm	850, 980, 1300, 1310, 1490, 1550, 1625 nm
Detector Type	Germanium (Ge)	InGaAs	Filtered InGaAs
Measurement Range	+6 to -60 dBm	+10 to -75 dBm	+26 to -50 dBm
Tone Detect Range	+6 to -50 dBm +6 to -45 dBm for 850 nm	+10 to -50 dBm +10 to -45 dBm for 850 nm	+6 to -30 dBm +6 to -25 dBm for 850 nm
Wavelength ID Range	+6 to -50 dBm +6 to -45 dBm for 850 nm	+10 to -50 dBm +10 to -45 dBm for 850 nm	+6 to -30 dBm +6 to -25 dBm for 850 nm
Accuracy ^b	±0.25 dB		
Resolution	0.01 dB		
Measurement Units	dB, dBm, µW		
GENERAL			
Power	2 x AA batteries, optional AC adapter		
Battery Life	300 hours		
Operating Temperature	-10 °C to 50 °C, 90 % RH (non-condensing)		
Storage Temperature	-30 °C to 60°C, 90 % RH (non-condensing)		
Size (H x W x D)	14.0 x 8.1 x 3.8 cm (5.5 x 3.2 x 1.5 in)		
Weight	0.26 kg (0.58 lb)		

Notes:

- a. All specifications valid at 25 °C unless otherwise specified.
- b. Accuracy measured at 25 °C and -10 dBm per N.I.S.T. standards.

Ordering Information

MODEL	INCLUDES
All OPM5 models	OPM5 optical power meter, 2 x AA batteries, protective rubber boot, USB cable, Windows® compatible software, and carry case.

Authorized Channel Partner



United States
 Customer Service
 1.800.321.5298
 1.603.528.7780
 www.AFLglobal.com

Europe, Middle East, Africa
 Max Penfold
 Max.Penfold@AFLglobal.com
 +44 1799 542 840
 +44 7802 839 160

Middle East
 Ahmed El Sakaty
 Ahmed.ELsakaty@AFLglobal.com
 +20 106 451 523

Africa (Sub Sahara)
 Nicholas Cole
 Nicholas.Cole@AFLglobal.com
 +44 7702 005 590

Greater China
 Dai Liu
 Dai.Liu@AFLglobal.com
 +86 133 1101 4533

Asia-Pacific (non-China)
 Saw Biing Huei
 Biing.Saw@AFLglobal.com
 +65 9791 3398